

9050N MONOCHROME LASER PRINTER



High performance up to 50 ppm

Tabloid printing

**High speed connectivity through
10/100BaseT Ethernet**

1200 x 1200 dpi print quality

Adobe® PostScript® 3™ standard

Performance monitoring via web page

PERFORMANCE, FLEXIBILITY, AND VALUE

POWER PRINTING

9050N laser printer delivers powerful performance at up to 50 pages per minute and exceptional image quality of 1200 dpi resolution. Additional features like private printing and web-based job accounting provide added security and accountability to the printing system.

The 9050N is available with up to six input trays to hold a variety of paper types, weights and sizes including transparencies, labels and cover stock. Save time by letting the printer prepare your documents for distribution with the collate, staple and hole punch finisher (or finishing) option.

Produce high-quality, customized transaction documents in one step with optional e-forms software. Monitor and modify data on-the-fly, with the powerful Intellifilter™ feature; legacy data streams can be modified and electronic forms can be triggered with this feature.

INTELLIPRINT CONTROLLER

The 9050 powered by Intelliprint® controller, delivers the highest quality for text, graphics, imaging and application portability across platforms. The optional hard drive provides four additional features which include job library (which provides password protected printing), job save, job collection and job accounting. These new features enable users to more efficiently manage and analyze their printing activities.

9050N MONOCHROME LASER PRINTER

Available Configuration.....9050: Available in 4 configurations

Print Speed50 ppm
Print MethodElectro-photographic semiconductor laser with Intelliprint controller
ProcessorMIPS R7000 600MHz
Resolution600dpi and true 1200dpi at full engine speed
Time To 1st PageLess than 6 Seconds
Memory256MB expandable to 768MB
Standard ConnectivityParallel (Bi-directional IEEE 1284), USB (v 2.0 Hi-Speed), Ethernet 10/100baseT, Serial RS -232/422
Standard EmulationPCL5c, PCL5e, PCL6, Adobe® PostScript® 3™, Adobe PDF (ver. 1.3)
Print MonitorEmbedded web server, TGNet Admin, PC Status Monitor
Fonts136 Adobe PostScript fonts; 86 PCL
ConsumablesToner Cartridge 33,000 pages, OPC Drum Cartridge 60,000 pages based on 5% coverage, Staples - 5k cartridge
Maintenance300K letter/A4
STD Paper HandlingTray 1: 100 sheet multi-purpose feeder (MPF); Tray 2 and 3: 500 letter/tabloid sheets each
Optional Paper HandlingTray 4 and 5: 500 sheets each of letter/tabloid, or, Tray 4 and 5: 1200 + 800 sheets letter, Tray 6: 2000 sheets A4/Letter
DuplexingOptional on 9050N, standard on 9050ND
Paper TypePaper sheets, envelopes, postcards, cardstock, labels, index cards, transparencies, and qualified carbonless paper; this device is suitable for processing recycled paper according to EN 12281:2002
Paper WeightTray 1 multipurpose: 16- 58 lb. bond, up to 80 lb. cover; Tray 2: 16-28 lb. bond, up to 40 lb. cover?; Tray 3: 16 to 58 lb. bond, up to 80 lb. cover; Tray 4-5 option: 16-58 lb. bond, up to 80 lb. cover; Tray 6 option: 16-58 lb. bond, 80 lb. cover; Duplex option: 16-43 lb. bond
Paper Size3.5"x 3.9" minimum size (tray 1); 11"x 17" maximum size; A3, A4, A5, A6, B5, B4-JIS, Letter, Legal, Executive, Oficio, Statement, Tabloid, Legal 13 (Folio), and custom sizes; envelopes - C5, DL, Com 10, Monarch

Paper Output500-sheet face-down standard, optional Finisher with 500 sheet bin (offsets and staples) and 3000 sheet bin (offsets, staples and punches)
Physical Weight97 lbs. (44 kg)
Physical Size25.2" x 21" x 19.6" (640 x 525 x 498 mm)
Power Voltage110V Model; 110-127VAC, 12A
Power ConsumptionLess than 10 watts in sleep mode, standby 100-110 watts, less than 1300 watts printing; (TEC) 8.92 kWh/week
ComplianceENERGY STAR® compliant, RoHS, Microsoft, ISO-Compliant, Meditech Approved
WorkloadUp to 300,000 pages per month
Forms SoftwareIntellifilter and TG Forms compatible
DriversWindows 2000, XP, Vista, Windows 7, Server 2003, Server 2008 Postscript 3 and PCL Drivers; Mac OSX; UNIX and LINUX Compatibility
TemperatureOperating: 41°F - 90°F (5° to 32°C)
HumidityOperating: 15%-85% non-condensing
AcousticPrinting - 54 dB(A); Standby - 22 dBA
WarrantyFor warranty information go to www.tallygenic.com
Option 1Hard Disk (40 GB or larger)
Option 2Compact Flash (2 GB)
Option 3BarCode Plus Extended CF Card

For further information about our products and services, please visit our website at: www.tallygenic.com

Southern Europe, Iberia & Middle East and Africa – PRINTRONIX France Sarl
 13 Rue Salomon de Rothschild, 92150 Suresnes, France
 Tel: +33 (0) 1 46 25 19 00

Northern Europe – PRINTRONIX UK Ltd
 Millars Brook, Unit 3, Molly Millars Lane, Wokingham, Berkshire
 Tel: +44 (0) 118 977 1000

For sales enquiries, please email: emeasales@printronix.com

Central & Eastern Europe – PRINTRONIX Deutschland GmbH
 Goethering 56, D-63067 Offenbach, Germany
 Tel: +49 (0) 69 82 97 06 0

Middle East and Africa
 Jebel Ali Free Zone, PO Box 262746, South Zone, Dubai
 Tel: +971 (4) 8137866

For technical support, please email: emeasupport@printronix.com

Russia and C.I.S. – PRINTRONIX Inc, Moscow Representative Office
 Balakirevsky per., 19, office 106, 105082 Moscow, Russian Federation
 Tel: +7 (495) 737 9387

Customer Support Centre EMEA – PRINTRONIX Netherlands BV
 Nieuweweg 283, P.O. Box 163, NL-6600 AD Wijchen, Netherlands
 Tel: +31 (0) 24 64 89 489

